

A 50,000 FT. OVERVIEW OF THE SYSTEM

Tigi

Serial Communication




Fig. 3

Opening Flag	Command Opcode	(optional) Parameters (optional) Data
0x7E	8 bits	

Fig. 4A

Opening Flag	Command Oncode	Length	Address	Data
0x7E	0x01	16 bits	32 bits	Length*8 bits

Fig. 4B

Opening Flag	Command Opcode	Length †	Address
0x7E	0x02	16 bits	32 bits

Fig. 4C

Opening Flag	Command Opcode	Open/Close, Address
0x7E	0x08	32 bits

Fig. 4D

Command	(optional) More Commands	* CRC *
0x7E, Opcode, etc	0x7E, Opcode, etc	16 bits

Fig. 4E

ID Word	hex 7E80 (16 bits)
Length	4*(N+4) (16 bits)
RPQE	4 longwords
Packet Data	N longwords
CRC-16	16 bits

Fig. 4F

ID Word	hex 7E81 (16 bits)
Length	hex 0038 (16 bits)
Raw Cell	14 longwords
CRC-16	16 bits

Fig. 4G

ID Word	hex 7E82 (16 bits)
Length	hex 0008 (16 bits)
*TSQE	2 longwords
CRC-16	16 bits

Fig. 4H

DRAWINGS P. 4055

ID Word	hex 7E02 (16 bits)
Length	4*(N+1) (16 bits)
Address	1 longword
Data	N longwords
CRC-16	16 bits

Fig. 4I